IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

Applicants: Simon P. VALENTINE, Christopher R. LINZELL,

Lee A. WALKER

Case: 3Com-81 (3022US)

Serial No.:

Filed:

Group Art Unit:

Examiner:

Title: EFFICIENT METHOD OF DEDUCING NETWORK TOPOLOGY

INCLUDING ENDSTATIONS

Commissioner for Patents **BOX PATENT APPLICATION** Washington, D. C. 20231

S I R:

SUBMISSION OF PRIORITY DOCUMENT

In connection with the above-captioned application, applicants enclose the following priority document to support their claim to priority:

UNITED KINGDOM - Appl. No. 0009045.6, filed April 12, 2000.

Respectfully submitted,

September 14, 2000

Peter L. Michaelson, Attorney

Req. No. 30,090

Customer No. 007265

(732) 530-6671

This Page Blank (uspto)

MICHAELSON & WALLACE Counselors at Law Parkway 109 Office Center 328 Newman Springs Road P.O. Box 8489 Red Bank, New Jersey 07701

EXPRESS MAIL CERTIFICATION

"Express Mail" mailing label number: **EL632363705US**Date of deposit: **September 15, 2000**

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Signature of person making certification

Peter L. Michaelson

Name of person making certification

This Page Blank (uspto)







The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ



CERTIFIED COPY OF PRIORITY DOCUMENT

e undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) e Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the ptroller-General, hereby certify that annexed hereto is a true copy of the documents as nally filed in connection with the patent application identified therein.

ordance with the Patents (Companies Re-registration) Rules 1982, if a company named certificate and any accompanying documents has re-registered under the Companies Act with the same name as that with which it was registered immediately before retion save for the substitution as, or inclusion as, the last part of the name of the words limited company" or their equivalents in Welsh, references to the name of the company ertificate and any accompanying documents shall be treated as references to the name ich it is so re-registered.

ance with the rules, the words "public limited company" may be replaced by p.l.c., P. C. or PLC.

eg ation under the Companies Act does not constitute a new legal entity but merely ect e company to certain additional company law rules.

Signed

obeiens.

Dated 8 May 2000

This Page Blank (uspto)

17APR00 E529333-8 D00016_ P01/7700 0.00-0009045.6

The Patent Office

Cardiff Road Newport South Wales NP9 1RH

Request for grant of a patent (See the notes on the back of titls form. You can also get an explanatory leaflet from the Patent Office to belower till in

this form)

Your reference

HRW/sb/3Com3022GB

2. Patent application number (The Patent Office will fill in this part)

112 APR 2000

0009045.6

3. Full name, address and postcode of the or of each applicant (underline all surnames)

3Com Corporation 5400 Bayfront Plaza M/S 1308 Santa Clara California CA95052 USA

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Delaware, USA

7656978000

4. Title of the invention

Efficient Method of Deducing Network Topology including Endstations

5. Name of your agent (if you have one)

BROOKES & MARTIN

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

HIGH HOLBORN HOUSE 52-54 HIGH HOLBORN LONDON WC1V 6SE

Patents ADP number (if you know it)

471001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number Country

Priority application number (if you know it)

Date of filing (day / month / year)

 If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application Number of earlier application

Date of filing (day / month / year)

 Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' If:

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

Patents Form 1/77



THE PAGE BLANK (USPID)

Patents Form 1/77	
 Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document 	
Continuation sheets of this form	0
Description	7
Claim (s)	1
Abstract	0
Drawing (s)	2 **
If you are also filing any of the following, state how many against each item.	
Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	1
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	1
Any other documents (please specify)	-
11	I/Mo request the grant of a natent on the basis of this application

Signature

Date

11 April 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

Hugh R Wright

01892 510600

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form

Patents Act 1977 Rule 15)



Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road Newport South Wales

			NP9 1RH
1.	Your reference	HRW/sb/3Com3022GB	
2.	Patent application number (if you know it)	12 APR 2000	9045.6
3.	Full name of the or of each applicant	3Com Corporation	
	1		
4.	Title of the invention	Efficient Method of Deducing Network Topology including Endstations	
5.	State how the applicant (s) derived the right from the inventor (s) to be granted a patent	By virtue of the employment of the inventors and their employment contracts	
6.	How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))		
7.		I/We believe that the person(s) name any extra copies of this form) is are the in which the above patent application Signature	nventor(s) of the invention
8.	Name and daytime telephone number of person to contact in the United Kingdom	Hugh R Wright	01892 510600

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.



Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Simon Peter VALENTINE 55 The Horseshoe Hemel Hempstead Hertfordshire **HP3 8QS** United Kingdom

7231511001

Patents ADP number (if you know it):

Christopher Robert LINZELL 1 Sandfield Road

St Albans

Hertfordshire

AL1 4JZ

United Kingdom

Patents ADP number (if you know it):

Lee Anthony WALKER 126 Estcourt Road Watford Hertfordshire WD1 2PZ United Kingdom

TSSOTTECH

Patents ADP number (if you know it):

Reminder

Have you signed the form?

EFFICIENT METHOD OF DEDUCING NETWORK TOPOLOGY INCLUDING ENDSTATIONS

BACKGROUND OF THE INVENTION

5

The present invention relates to a method and apparatus for deducing network topology.

10

The present invention relates to the process of discovery of the devices on a network, that is a network of electronic devices comprising, for example, workstations, personal computers, servers, hubs, routers, bridges, switches, (hereinafter referred to as devices of the network), and links between these devices which may be in the form of physical cable or wireless links. The network may be a local area network (LAN), such as an Ethernet network, wide area network (WAN) or other types, including wireless networks.

15

Computers and other devices connected to a network may be managed or unmanaged devices. A managed device has processing capability, which enables it to monitor data traffic sent from, received at, and passing through the ports of the device.

Monitored data associated with the ports of the network device is stored in memory on the network device. For example, data relating to the origin of a data packet which is received at a port is stored along with the identity of the relevant port.

25

20

After such a network has been installed, it is desirable for the person appointed network manager to be able to understand the technical operation of the network. In known network management systems, the manner in which the relevant data is retrieved from the managed devices, compiled and displayed ("discovered") has been problematic in several respects.

30

The topology of the network may be deduced by the network manager's computer by the process of discovery in which each of the devices of the network is interrogated to thereby produce on a network manager's workstation details of the network and its operation, preferably in the form of a network map which may be displayed on a visual display unit showing the devices and links between the devices. At its simplest, and where the device is a "managed" device, this information is usually provided by interrogation using a known protocol, such as the SNMP (Simple Network Management Protocol), of the so-called 'agent' of each device which stores the device's unique MAC address, the type of device and the MAC addresses embedded in the data passing into a particular port which thereby gives the MAC addresses of the origin of the data and hence the MAC address of the devices which are connected to the ports directly or indirectly.

10

15

5

One particular problem is that in any but the simplest of networks, the discovery procedure can be very slow in view of the large number of interrogations required.

It would be desirable to reduce the number of interrogations required to speed up the discovery process.

SUMMARY OF THE INVENTION

20

The present invention provides a method for discovering the topology of a network comprising:

initially resolving the positions of the end stations, and subsequently resolving the topology of the remaining devices.

25

The present invention also provides a computer program on a computer readable medium loadable into a digital computer or embodied in a carrier wave, said program including software for carrying out the method of the preceding paragraph.

30

The present invention also provides a computer program on a computer readable medium loadable into a digital computer or embodied in a carrier wave, for discovering the topology of a network comprising:

a program step to query a port of a managed device for a first address of any packet which has been received;

5

10

25

30

a program step for querying the same port of the device for a second address of any packet which has been received;

if there is no second address, returning relevant data to a manager and determining if there is another port on the device;

if there is a second address, determining if there is another port on the device; if there is another port on the device, repeating the preceding four steps for another port of the managed device:

if not, repeating the preceding five steps in respect of another managed device.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred embodiment of the invention will now be described by way of example only and with reference to the accompanying drawings in which:-

Figure 1 shows a network to be discovered,

Figure 2 is a table of learnt addresses for each port, and

Figure 3 is a flow chart of a program for carrying out the preferred method of the invention.

20 DESCRIPTION OF THE PREFERRED EMBODIMENTS

The physical network to be discovered may comprise a plurality of devices in the form of a network supervisor's workstation or computer, other workstations, hubs, or switches.

The devices are connected together by means of links which may be hard wired or wireless and utilise any desired protocol.

The network supervisor's workstation includes, in addition to a visual display unit, a central processing unit or signal processor, a selector which may be in the form of a mouse, a program store which may comprise, for example, a CD drive, a floppy disk

()

5

10

15

20

25

30

drive or a zip drive, and a memory for storing a program which may have been loaded from the program store or downloaded for example via Internet from a website.

To discover the network, using SNMP, the network supervisor's computer interrogates each device and analyses the network, and stores in the memory the information relating to the devices within the network and the links between the devices. In essence, managed devices include a so-called agent which in the case of an SNMP agent stores information about the device such as its unique MAC address, its sysObject ID (which identifies what the device is and its model type), how many ports it has, and the MAC address of the origin of the data which at least some of the ports have received and hence to which they are directly or indirectly connected. The computer interrogates the agents of each device.

In a preferred arrangement, the computer may, on command from the selector, process signals from the memory by the signal processor and provide on the visual display unit a network map showing each of the devices and the links therebetween. In the examples described, the network is simple but of course in many instances the network will be considerably more complex and it may be necessary to arrange that the visual display unit only shows a simplified version or only part of the network at any one time.

Figure 1 shows an example of a simple network topology. The managed devices which may be switches and hubs are represented by the rectangles labelled A – D. Each device has three or four ports labelled, for example, A1, A2, A3, B1, B2, B3, B4. End stations, that is devices which have only a single connection to the network and are typically Personal Computers or workstations, are represented by squares R – Z. As is well known the ports of a managed device will learn the source MAC addresses of any packets of data that pass through them from another device. Referring to Figure 2, there is set out a table listing each of the ports of Figure 1, and the addresses learnt by each port and which is stored on the relevant agent. Thus port A1 will learn all of the addresses of device B and the devices to which it is attached and will thus learn the MAC address of B, X, Y, Z. Note that to simplify the

5

10

15

20

25

30

explanation, the table assumes that any packet transmitted by a device is seen by all nodes downstream of it. In a switched network this may not necessarily be the case.

In order to determine the topology of the network, as already explained, the network manager's computer queries each managed node to determine the addresses of other nodes on the network to which it has been connected. This would include the address of all other managed nodes and the end stations. This type of request normally involves interrogating all of the end stations (one request per address) or interrogating each address (again potentially one request per address). This data can then be used to determine the relative locations of all of the nodes on the network.

In order to reduce the number of interrogations or requests, we arrange for the position of the end stations to be resolved before attempting to deduce the relative positions of the managed devices. This can be done by querying each managed device to return details of any ports that have only learnt one address and to return that address. Thus in the example of Figure 1, such ports would be B1, B3, B4, C2, C3, C4, D2, D3, and D4 (ie those ports are connected to end stations). In order to obtain this information, two requests per port are made, one to obtain the first address, and another to determine if there is a second address. In the example given, this means that for each of B, C and D, eight requests (two times the number of ports) are made per device in order to determine the attached end stations. This request procedure replaces in the prior art the one request per end station (a total of nine).

In a real network there is likely to be significantly more end stations than managed devices and ports on a device. For example, in a network of twenty managed devices and four hundred end stations, where each device has approximately 20 ports in use, to resolve the end stations for each managed device would require about forty requests rather than a total of four hundred requests to cover all of the end stations using the prior procedure.

Having resolved the end stations, the discovery of the remaining managed devices can proceed. Thus it is only necessary to discover the relative positions of the managed

devices. To do this only requires a small number of requests per device. For example, for device A, the query "which ports have learnt the addresses of device B, C or D?" would be made which would require only three requests (ie the topology of the end station is already known).

5

(; ,

The preferred method of the invention is carried out under the control of the network manager's workstation or computer and in particular by means of a program controlling the processor apparatus of that computer or elsewhere in the system.

10

15

The program for controlling the operation of the invention may be provided on a computer readable medium, such as a CD, or a floppy disk, or a zip drive disk carrying the program or their equivalent, or may be provided on a computer or computer memory carrying the website of, for example, the supplier of the network products. The program may be downloaded from whichever appropriate source and used to control the processor to carry out the steps of the invention as described.

The program may include an algorithm of the form set out in the flow chart (Figure 2) of the drawings.

20

Thus the program may include the following steps:

program step 101, network manager's computer polls a managed device; program step 102, query a port of the device for a first MAC address of any packet which has been received;

25

program step 103, query the same port of the device for a second MAC address of any packet which has been received;

if there is not a second MAC address, (ie the first MAC address is an end station) in program step 104, return relevant data to manager and go to step 105;

if there is a second MAC address, go to step 105;

30

in step 105, is there another port on the device?;

if yes, go to program step 102;

if no, go to program step 106;

in program step 106, is there another device?; if there is another device, go to program step 101; if there is not another device, go to step 107; in program step 107, resolve the managed devices.

5

The invention is not restricted to the details of the foregoing example.

CLAIMS

- A method for discovering the topology of a network comprising:
 initially resolving the positions of the end stations, and subsequently resolving
 the topology of the remaining devices.
 - 2. A method as claimed in claim 1 in which the step of initially resolving the positions of the end stations comprises, for each managed device, determining which ports are only connected to an end station.

10

3. A method as claimed in claim 1 or claim 2 in which the step of resolving the topology of the remaining devices comprises:

querying for each managed device, which ports have learnt the address of another managed device.

15

4. A computer program on a computer readable medium loadable into a digital computer or embodied in a carrier wave, said program including software for carrying out the method of any of claims 1 to 3.

20

5. A computer program on a computer readable medium loadable into a digital computer or embodied in a carrier wave, for discovering the topology of a network comprising:

a program step to query a port of a managed device for a first address of any packet which has been received;

25

a program step for querying the same port of the device for a second address of any packet which has been received;

if there is no second address, returning relevant data to a manager and determining if there is another port on the device;

if there is a second address, determining if there is another port on the device;

30

if there is another port on the device, repeating the preceding four steps for another port of the managed device;

if not, repeating the preceding five steps in respect of another managed device.




Fig. 1 Topology Example

Port	Learnt addresses
A1	l B, X, Y, Z
A2	D, R, S, T
A3	C, U, V, W
81	Z
82	A, C, D, R, S, T, U, V, W
B3	Y
84	Z
C1	A, B, D, R, S, T, X, Y, Z
C2	U
C3	V
C4	W
D1	A, B,C, U, V, W, X, Y, Z
D2	R
D3	18
D4	T

Fig. 2 Learnt Addresses

